

Silent+ Mini Orange



Revolutionizing Mini Pumps
The First with Variable Speed Technology

FP3430/MG
Condensate Removal Pump

Key Features:

- Flexible for all applications; ideal for ceiling voids and ducted systems
- Eliminates the need for additional noise or vibration dampers
- Adaptive variable speed flow with intelligent capacitance sensing
- As low as 16 dB(A)
- 3-year warranty

Range Suitability:

- 40kW / 136,000BTU/h / 11.37 tons
- High wall ducted units, floor standing and chassis units
- Perfect for- smaller commercial and residential applications where quiet is needed

In the Box:

- Silent+ Mini Orange 5th Gen Pump
- Reservoir (incl. filter and lid)
- 5' (1.5m) Plug and Play Cable**
- 5' (1.5m) Clear PVC Tube
- 6" (152mm) Clear Vent Hose
- 8.5" (220mm) Orange Inlet Hose
- Drain connector kit: Straight connector and rubber elbow
- Fixing Pad
- Universal Pump Mount
- Quick Start Guide

The World's best selling mini pump offers adaptive variable flow, unrivalled reliability and performance.

Product Specifications:

Max. flow	9.25 US Gallons (35L/h) @ 0m head
Max. rec. head	33ft./10m
Max. suction lift	6'/1.5m
Min. dB(A) @ 1m	16dB(A)*
Power supply	100-250V, 50/60Hz, 0.18A, 2.4W
Rated	Continuous
Class	II
Max. unit output	40kW / 136,000BTU/h / 11.37 tons
Max. ambient temp	104°F (40°C)
IP Protection	IP24
Inlet o/d	5/8" (16mm)
Outlet o/d	1/4" (Ø6mm)
Safety switch	High level safety wires N.C. contacts, 250 VAC, 3A max
Self priming	✓

*Assuming solid wall construction with a 2kW unit.

**Not backwards compatible

Ensure ALL cleaning chemicals are flushed out of the reservoir after use.

Silent+ Mini Orange | 100-250VAC, 50Hz/60Hz

