

## **G535 DIRECT DRIVE SUBMERSIBLE PUMP**

## FOR 115V,60Hz or 230V, 50/60Hz

Beckett's submersible pump line offers top of the line epoxy encapsulated (not oil filled), 115V,60Hz or 230V, 50/60Hz design to meet all your continuous duty requirements. They are low maintenance, environmentally safe, and can be used in a variety of industrial applications. Each pump features a heavy-duty motor for maximum output and reliability.

## FEATURES:

chus for G535A

**(** for G535C

- Submersible
- UL listed
- 6ft. power cord
- Corrosion resistant materials
- Low maintenance high torque motor
- 1/2" MNPT discharge, fits 3/4" ID PVC tubing





Model #	н	w	L	Outlet	Inlet	Volts	Amps	Watts	Gallons per hour @ 230V, 60Hz				Max Lift	Weight Lb.	ο Γι.	c (UL) us	CE		
									1′	2′	4′	6'	8'	10′	(Ft.)	Each	Cord		
G535A	4"	4"	5 3/8"	1/2" MNPT, 3/4" I.D. Hose	Screen	115	1.2	75	550	520	450	390	295	210	13	4.1	w/Plug	$\checkmark$	
G535C	4"	4"	5 3/8"	1/2" MNPT, 3/4" I.D. Hose	Screen	230	0.7	75	585	545	500	425	340	250	13.2	4.2	No Plug		$\checkmark$

DESIGNED FOR SUBMERSIBLE USE ONLY

beckett

Driven by Innovation Since 1948.

Average Performance

## BeckettUS.com | Tel: 888-232-5388

© 2023 Beckett Corporation. All Rights Reserved. Version 2022-10-21