

Wireless Lodge Watch

This wireless energy monitor is designed to reduce wasted energy by as much as 40% in vacation rental properties. The iO-LW detects when a door or window is left open for more than 2 minutes. The iO-LW then locks out the HVAC equipment until it detects the closure of the door or window for 2 minutes. This saves on energy costs, but also reduces short cycling of the HVAC equipment, reducing equipment icing, condensate pan overflow and wear in the equipment. Available for up to 4 doors and/or windows can be added. Call for specifications on systems requiring more than 4 transmitters.

Warranty: 5 years



Specifications:

Transmitter Dimensions	1.00" Height x 3.40" Width x 0.57" Depth
Control Module Dimensions	5.00" Height x 6.00" Width x 1.5" Depth
Transmitter Power	3V alkaline battery (included)
Control Module Power	24 VAC
Operating Temperatures	32° F to 120° F
Encoding	16 million combinations, pulse-width modulation
Frequency	315MHz and 433.92MHz or according to local requirements
Compliance	FCC Part 15k, MPT 1340 and Directive 1999/5/EC



5351 East Thompson Road Suite 142
Indianapolis, IN 46237
P: 888.359.0362
F: 317.489.5204
info@iOhvacsystems.com
www.iOhvacsystems.com

