

NX1G

NX1GV

NEXUS 2 Digital Manifold Gauge

 **PATENT PENDING**



Touch • Read • Master

Powerful Visual w/ HD Color Interface

- Choose your work style from four themes: Classic, America, Galaxy, Daylight
- Convert data into visuals with enhanced UI
- Self-explanatory interface
- Highly responsive 5.5" touch screen

Rugged and Reliable

- Shock-absorbing corner protection
- Heavy-duty shell & aluminum body
- IP54 rated for harsh conditions

Precision, Smart and Wireless

- Class 0.4 accuracy with digital display
- Bluetooth connections with temp clamps & micron gauge
- Work with *myNAVAC* App & *MeasureQuick*
- Supports over 100 refrigerants, updatable via App

Multiple Operation Modes

- Manifold Gauge mode with SH/SC display
- Leak Test mode
- Evacuation mode with decay test function
- Touchscreen navigation for faster operation

Ease of Use

- 1/4 turn ball valves & swivel ports
- Rechargeable lithium battery w/ quick charge
- Adjustable brightness

Portability

- Multi-purpose carry case
- Folding hook for portability
- Extension canvas hook

Model	NX1G (Vacuum Gauge Not Included)	NX1GV (Vacuum Gauge Included)
Refrigerant Type	R11, R113, R114, R115, R116, R12, R1224yd(Z), R123, R1233zd, R1233zd(E), R1234yf, R1234ze, R1234ze(Z), R124, R1243zf, R125, R13, R134a, R1409A, R22, R23, R236fa, R245fa, R290, R32, R401A, R401B, R401C, R402A, R402B, R403A, R403B, R404A, R405A, R406A, R407A, R407B, R407C, R407D, R408A, R41, R410A, R410B, R411A, R411B, R412A, R413A, R414A, R414B, R415A, R415B, R416A, R417A, R417C, R420A, R421A, R421B, R422A, R422B, R422C, R422D, R424A, R427A, R428A, R434A, R437A, R438A, R447A, R447B, R448A, R449A, R450A, R451A, R451B, R452A, R452B, R452C, R453A, R454A, R454B, R454C, R455A, R456A, R458A, R459A, R459B, R460A, R460B, R500, R501, R502, R503, R507A, R508B, R513A, R600, R600a, R601, R601A	Firmware can be updated at NAVAC website or with <i>MyNAVAC™</i> App
Screen Configuration	IPS touch screen, 1024 x 512 pixel	
Ports	(3) 1/4" sae	
Maximum Manifold Pressure	1087 psi (7500 kPa)	
Bluetooth Range	260 ft (80m) line of sight	
Power Supply	Rechargeable 3000mAh lithium battery, 8~100 hours run time, Type-C charging port	
Language	English, Spanish, French	
Accessory	Bluetooth Temperature Clamps NST1 (Low Side), NST2 (High Side), Charging Cable, Storage Bag	NMV1S Vacuum Gauge in addition to the NX1G Kit

2-YEAR WARRANTY