



## STARTEK

**Item Number 4507917**

Electronic, compact leak detector for all halogenated refrigerants

- Detects all halogen-based refrigerants
- Device complies with SAE J1627, EN 14624 standard
- Easy handling thanks to one-button operation
- Sensitivity levels selectable with double click
- Automatic recalibration
- Leakage is indicated by optical and acoustic signals
- Auto-Shutoff
- In a practical holster with belt clip
- Replacement sensor in battery compartment
- In a sturdy plastic case

## Technical Data

<b>Color</b>	green (RAL 6026)   yellow (RAL 1023)
<b>Standards</b>	SAE J1627 EN 14624 EN 61326-1:2013 EN 55011 :2018-05 EN 61000-4-2 :2009-12 EN 61000-4-3 :2011-04 EN 50581:2012
<b>RoHS Conformity</b>	Yes
<b>Refrigerant(s)</b>	R12   R134a   R22   more
<b>Operating Temperature Range</b>	32 - 122 °F
<b>Battery</b>	2 x AA
<b>Operating Hours</b>	40 h
<b>Sensitivity</b>	< 0.1 oz/yr

Acknowledged globally



<b>Refrigerant Type</b>	Refrigerants   CFC   HCFC   HCF   HFO
<b>Measurement Technology</b>	Negative Corona
<b>Tube Length</b>	12 "
<b>Scope of Supply</b>	Batteries   Case   Instruction manual
<b>Packaging</b>	Sturdy plastic case
<b>Warm-up Time</b>	2 s

## Spare Parts

4507577	ES-02/2	Replacement sensors for STARTEK leak detector, 2 pieces
---------	---------	---