



721 Combustible Gas Leak Detector with LCD Display

Features

- Combustible Gas Leak Detector capable of displaying real ppm, stepped ppm, and %LEL (Lower Explosive Limit).
- 10ppm sensitivity (methane)
- Detect combustible gases including natural gas, propane, butane, etc.
- Thumbwheel adjustable tic rate to locate leaks quickly and accurately.
- Two line display with bargraph and backlight
- Audio / Visual alarm indication with user adjustable alarm point.
- Visual alarm indicator in sensor housing
- Earphone jack for use in noisy environments.
- Approximately 20 hours of continuous use (C cell alkaline batteries x2)



Specifications

Leak Detection Sensitivity (methane):	10ppm
Display Type:	Dual display with analog bargraph and backlight
Display Modes:	Real (ppm), Leak Level (stepped ppm), %LEL
Ranges:	
Real ppm:	0 to 9999ppm
Stepped ppm:	0, 500, 1000, 3000, 5000, 9999ppm
%LEL:	0 to 19.9%
Audible Leak Indication:	Adjustable tic rate via side thumb wheel
Alarm Indication:	Visual and audible (User adjustable alarm level)
Sensor Test and Zero:	Automatic at start up
Goose Neck:	16" long
Size:	9.4" x 2.9" x 2.2" (240mm x 74mm x 55mm)
Weight:	1 lb (454g)