



# Residential/Commercial Combustion Analyzer w/ Pressure



BACKED BY

**UEi**  
SERVICE+

## Functions

- Measures: CO, CO2, Differential Pressure, Flue and Inlet Temperature
- Calculates: O2, Differential Temperature, Efficiency (Net, Gross), Excess Air

**10**  
YEAR  
WARRANTY

## Features

- Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- DMM-style user interface
- Over-range protection pump
- NOx Filtered CO Sensor
- Heat Exchanger Test
- Large 6 Line backlit Display
- Water Trap Indicator
- High Altitude Compensation
- Low Flow Detection to protect reading accuracy



## Includes

- Rechargeable batteries 3 (AA)
- Probe (CP2)
- USB Charging cable (AAC5)
- Particle Filter (spare) (17631)
- Tubing w/ connector (11000)
- K-Type Thermocouples ATT29 (2)
- Quick Start Guide (201996)
- Carry case (AC509)



## Specifications

### TEMPERATURE MEASUREMENT

Parameter	Range	Resolution	Accuracy
Flue Temperature	32° to 1112°F (0° to 600°C)	0.1°F (0.1°C)	±(0.3% rdg +3.6°F (2°C))
Inlet Temperature (Internal Sensor)	32° to 122°F (0° to 50°C)	0.2°F (0.1°C)	±2°F (1°C)
Inlet Temperature (External Sensor)	32° to 1112°F (0° to 600°C)	0.2° (0.1°C)	±2°F (1°C)

### FLUE GAS MEASUREMENT

Parameter	Range	Resolution	Accuracy
Carbon Monoxide	0 to 2000 ppm	1 ppm	±3 ppm or ±5% rdg (whichever is greater)
(Optional H2 Compensated)	2000 to 10000 ppm	1 ppm	±10% rdg
Carbon Dioxide	0 to 20%	0.1%	±0.3% volume

### CALCULATIONS

Parameter	Range	Resolution	Accuracy
Oxygen	0 to 21%	0.1%	±0.3% volume
CO/CO <sub>2</sub> Ratio	0 - 0.9999	0.0001	±5% rdg
Efficiency (Net or Gross)	0 to 99.9%	0.1%	±1% rdg
Efficiency High (C)	0 - 119.9%	0.1%	±1% rdg
Excess Air	0 to 119.9%	0.1%	±0.2% rdg

### PRESSURE (DIFFERENTIAL)

Parameter	Range	Resolution	Accuracy
Pressure (Differential)	±32" H <sub>2</sub> O	0.1mbar	±0.5% FSD

<b>Pre- Programmed Fuels</b>	Natural Gas, Propane, LPG, Light Oil, Heavy Oil, Bio Oil, Pellets
------------------------------	---

<b>Battery Life</b>	>8 hours (continuous with pump on)
---------------------	------------------------------------

<b>Certification</b>	The C161 is TUV-tested and certified to EN 50379, Parts 1-3 in accordance to 1st German Federal Emission Control Ordinance (BimSchV)
----------------------	--

### Operating Conditions

<b>Temperature</b>	32° to 113°F (0° to 45°C)
<b>Humidity</b>	15% to 90% R.H.

<b>Storage Temperature</b>	0° to 113°F (-18° to 50°C)
----------------------------	----------------------------

<b>Power Supply</b>	Rechargeable Batteries, USB Charging
---------------------	--------------------------------------

### Downloads



### Data Sheet



### Manual



Made in UNITED KINGDOM

