# **YJACK® Series Wireless Probes**



# YJACK® FOR A MORE CONNECTED TECH.



The YJACK® Series is a network of devices that form a complete platform offering a total HVAC/R diagnostics solution. Multiple devices can measure system and environmental parameters, providing a complete picture of a system's condition.

Each device utilizes Low Energy Bluetooth® (BLE) technology to interconnect with each other and any smart device, Android™ or iOS. Many of the YJACK® Series devices communicate directly with TITANMAX™ and P51-870 TITAN® Digital Manifolds.



### YJACK® SERIES WIRELESS PROBES





### **Network of Wireless Devices for a Total HVAC/R Diagnostic Solution**

YJACK VIEW® App and measureQuick® App\* provide seamless integration with YJACK® Probes, TITANMAX™ and P51-870 TITAN® Digital Manifolds.





\* See select YJACK® Probes compatible with measureQuick® App.

### YJACK FLOW™ Anemometer NEW!

- Measures and displays duct air speed readings in fpm, f/s, m/s and m/m
- Automatically calculates quantity and location of readings in ducts





67068 YJACK MANO® Manometer



Display readings on the local display or remotely with the YJACK VIEW® App

**YJACK MANO® Manometer** 

Measures static pressure up to +/- 60 inches of

Pressure probe tips and

adapters included for

accurate duct and gas pressure measurements

water column

Current Sensor Accuracy: +/-1% of reading or +/- 0.15 Amps

**67067 YJACK AMP® Current Probe** 



### YJACK VAC® Vacuum Gauge

- System vacuum meaurement from atmospheric pressure to 1 micron
- Robust sensor resists pressure shock and oil contamination

67066 YJACK VAC® Vacuum Gauge

### YJACK DEW® Psychrometer

Measures percent relative humidity, dry bulb temperature, wet bulb temperature and dew point temperature



### **YJACK PATH® Range Extender**

- Connects and rebroadcasts up to (6) YJACK® probes and P51-870 TITAN® Digital Manifolds
- Adds up to additional 400 ft lineof-sight signal range per device

67060 YJACK PATH® Range Extender





- Measures surface temperature of pipes up to 1.25" diameter
- Temperature clamp provides strong, secure connection to system





### **YJACK® Temperature Strap**

- Measures surface temperature of pipes up to 6" diameter
- Elastic strap for secure connection

**67062 YJACK® Temperature Strap** 



### **YJACK PRESS® Pressure Gauge**

- Measures system pressure up to 725 psig (50 bar)
- 45° x 1/4" quick-coupler fitting for versatile system attachment

**67065 YJACK PRESS® Pressure Gauge** 





#### **YJACK VIEW® HIGHLIGHTS:**

- Compatible with all YJACK®, TITANMAX™ and P51-870 TITAN® devices (firmware version v4.0 or later)
- Freely navigate between available session types and multiple sessions at one time
- Psychrometric System Efficiency and Leak Test sessions and communication capabilities with YJACK PRESS®, YJACK VAC® and YJACK AMP® in v3.0+; YJACK MANO® update to v4.0+
- **Easily place and monitor status of all YJACK®, TITANMAX™** and P51-870 TITAN® devices from one screen
- Adjustable datalog formatting, multiple sampling intervals
- Generate customized and detailed service reports capturing system readings and equipment information



#### **YJACK VIEW® SMART APPLICATION:**

- Measure HVAC/R system pressure, temperature, saturation temperature, superheat and subcooling
- Monitor system evacuation status
- Check indoor air comfort and system efficiency with psychromeric air calculations: percent relative humidity, dry bulb, wet bulb and dew point temperature measurements
- Perform system leak tests and track pressure change over time
- Measure system charge with scale weight readings during charging and recovery operations
- Take electrical current measurements and analyze critical system power information
- Identify duct pressure changes and measure regulator gas pressures
- Generate highly customized and detailed service reports capturing system readings and equipment information
- Monitor status of all nearby YJACK®, TITANMAX™ and P51-870 TITAN® devices
- Freely switch between multiple simultaneous sessions without loss of data
- Customize data view for each measurement in traditional number format or graphically
- Create data logs to be saved or emailed from your smart device

 Choose from relevant refrigerant profiles found in the REFPROP database

 Available on iOS (version 10 or later) and Android<sup>™</sup> (version 8 or later) smart devices

#### **CREATE SERVICE REPORTS**

Service report feature creates highly customizable PDF reports of system measurements and service information while storing previous jobs and reports.

#### **ENHANCED DATA LOGGING**

Record data from one or all current session types. Choose from a variety of sampling rates depending on user need. Live updates to selected devices, units, elevation and refrigerant selection appended to existing data logs. Start and stop data logging at will — save for later or share via email for remote analysis.

#### STATIC PRESSURE SESSION

Displays pressure readings from YJACK MANO® for measurement of duct pressure changes and regulator gas pressure.



<b>a a o</b>		
psig		R-410A
124.6	psig	<b>267.0</b> psig
SYSTEM TEMPERATURES  LOW PRESSURE HIGH PRESSURE		
62.1	۰F	83.4 <sub>°F</sub>
SATURATION TEMPERATURES  VAPOR LIQUID		
42.3	°F	87.7 <sub>°F</sub>
SYSTEM PROPERTIES  SUPER HEAT SUB COOLING		
19.8	°F	4.2 <sub>°F</sub>
T: 12.0 °F	SYSTEN	

#### PRESSURE / TEMPERATURE

View system pressure and temperature data as reported by combination of YJACK PRESS®, temperature clamps, TITANMAX™ or P51-870 TITAN®. Easily select and favorite commonly-used refrigerants for calculating system properties including saturation temperatures and calculated system superheat/subcooling. Effortlessly manipulate data view types, including traditional large numeric format, analog gauge (pressure only) or graphically.

## PSYCHROMETRIC SYSTEM EFFICIENCY

Analyze psychrometric data reported by (2) YJACK DEW® devices. Ensure maximum comfort through wireless supply and return relative humidity, dry bulb, wet bulb, dew point temperatures and enthalpy calculations. Compare systemrated capacity to actual output for overall system efficiency.

#### **EVACUATION**

Monitor system vacuum as reported by a P51-870 TITAN® external wired vacuum sensor or the YJACK VAC® Wireless Vacuum Gauge. Data can be displayed as traditional large numeric format, analog gauge or graphically. Adjustable vacuum pressure target and hold timer ensures all non-condensable gases are removed from the system during evacuation.

#### **LEAK TEST**

Monitor pressure changes during nitrogen leak testing to verify that system is tight and view system pressure trends.

#### **CHARGING & RECOVERY**


Display scale readings from the Wireless Charging Scale (P/N 68864) to accurately charge systems or to determine system charge amount through recovery.

#### **ELECTRICAL**


Electrical session displays readings from YJACK AMP® Wireless Current Probe while calculating power draw and system Energy Efficiency Ratio (EER).

#### ANEMOMETER NEW

Automatically calculates quantity and location of readings in rectangular and circular ducts. Complete single line recordings for duct flow comparisons.











### YJACK® KITS



YJACK® Temperature **Clamp Kit** 



YJACK® Temperature/ **Humidity Kit** 



YJACK® Charging Kit



YJACK® Charging & Air Kit



67074 **YJACK® Charging & Evacuation Kit** 



#### **YJACK VIEW® APP SUPPORTED YELLOW JACKET® DEVICES:**

- TITANMAX<sup>™</sup> Digital Manifold
- P51-870 TITAN® Digital Manifold
- YJACK PATH® Range Extender
- YJACK PRESS® Pressure Gauge
- YJACK VAC® Vacuum Gauge
- YJACK AMP® Current Probe
- YJACK® Temperature Clamp YJACK® Temperature Strap
- YJACK DEW® Psychrometer
- YJACK MANO® Manometer
- YJACK FLOW<sup>™</sup> Anemometer
- · Wireless Refrigerant Scale

(P/N 68864)

YJACK VIEW® App Apple/App Store



☐iPhone ☐iPad

YJACK VIEW® App Android™/Google Play













- iPhone and iPad are registered trademarks of Apple Inc., registered in the U.S. and other countries.
- Android is a trademark of Google Inc.

  The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Ritchie Engineering is under license



### TITANMAX™ DIGITAL MANIFOLD KIT WITH YJACK® WIRELESS PROBES

#### **40887 KIT INCLUDES:**

- YJACK® Vacuum Gauge (P/N 67066)
- Set of (6) 60" PLUS II™ Manifold Hoses:
  - (3) RYB compact ball valves (P/N 29985)
  - (1) Y 3/8" str x 3/8" 45° (P/N 18160)
  - (2) Compact ball valve 1/4" x 5/16" (P/N 29425 and 29465)
- (2) YJACK® Temperature Clamps (P/N 67061)
- USB-C Charging/Data Cable (P/N 40847)
- Backpack multi-pocket (P/N 40845)



UPC#	Description	
67060	YJACK PATH® Range Extender	
67061	YJACK® Temperature Clamp	
67062	YJACK® Temperature Strap	
67063	YJACK DEW® Psychrometer	
67065	YJACK PRESS® Pressure Gauge	
67066	YJACK VAC® Vacuum Gauge	
67067	YJACK AMP® Current Probe	
67068	YJACK MANO® Dual Port Manometer	
67069	YJACK FLOW™ Anemometer <b>NEW!</b>	
67070	YJACK® Temperature Clamp Kit: (2) YJACK® Temperature Clamps, (1) YJACK PATH®	
67071	YJACK® Temperature/Humidity Kit: (2) YJACK® Temperature Clamps, (2) YJACK DEW® Psychrometers, (1) YJACK PATH®	
67072	YJACK® Charging Kit: (2) YJACK PRESS® Pressure Gauges, (2) YJACK® Temperature Clamps	
67073	YJACK® Charging & Air Kit: (2) YJACK PRESS® Pressure Gauges, (2) YJACK® Temperature Clamps, (2) YJACK DEW® Psychrometers	
67074	YJACK® Charging & Evacuation Kit: (2) YJACK PRESS® Pressure Gauges, (2) YJACK® Temperature Clamps, (1) YJACK VAC® Vacuum Gauge	
40887	TITANMAX <sup>™</sup> Manifold, YJACK VAC® Vacuum Gauge, YJACK® Temperature Clamps (2), USB-C Cord, Set of (6) PLUS II <sup>™</sup> Hoses; Backpack <i>NEW!</i>	